



7/16 DIN Male RA Connector for 1/2" Feeder Cable

Electrical & Mechanical Specifications		
Frequency Range	DC 7.5 GHz	
Characteristic Impedence	50 Ω	
VSWR	≤1.10@DC-3000MHz	
Insertion Loss	≤0.10dB@2200MHz	
Intermodulation 3rd	≤ -157dBc@2×20W	
Dielectric Withstanding Voltage	4000V rms,50Hz,at sea level	
Working Voltage	2700V RMS,50Hz,at sea level	
Dielectric Resistance	≥10000MΩ	
Contact Resistance	Center Contact ≤0.4mΩ Outer Contact ≤1.0mΩ	
Durability	Mating cycles ≥500	
Material & Plating		
	Material	Plating
Body	Brass	Tri-alloy
Insulator	PTFE	-
Center Conductor	Phosphor bronze/Beryllium Bronze	Au/Ag
Environmental		
Temperature Range	-40°C~+85°C	
RoHS	Compliant Yes	

Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059

+91-9027232570, +91-8800726650 ✉ info@srfsteleinfra.in, info@srfsteleinfra.com

🌐 www.srfsteleinfra.in