


SRFS TELEINFRA

4G Rubber Magnetic Antenna

Get connected with us:



Electrical Specifications	
Antenna Frequency	690 ~ 960; 1710-2690 MHz
Gain	≤6 dBi
VSWR	≤2.0
Impedance	50Ω
Polarization	Vertical
Radiation Direction	Omni Directional
Lightning Protection	Direct Ground
Maximum Input Power	100 W
HPBW	H:360°; V: 30°/40 °
Mechanical Specifications	
Cable	RG174, 1 Mtr or Customized
Connector	SMA (M) or Customized
Antenna Mount	Magnetic Base Mount
Antenna Length	±11 mm
Magnetic Base Dia	±30 mm
Operating Temperature(°C)	-40 +/- 85
Humidity	5~95%
Environmental Friendly	ROHS Compliant
IP Rating	IP65



Elevation Pattern
Referenced to 0 dBi

Add: plot no 10 shiv vihar a block Najafgarh Sahibi river road Vikasnagar Uttam nagar new delhi-110059

+91 84354 74330 info@srfsteleinfra.in, aayush@srfsteleinfra.in

www.srfsteleinfra.in, www.srfsteleinfra.com

SRFS Teleinfra | All specifications are subject to change.
SRFS reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.
It may be necessary to make modifications to the part and/or the documentation of the part to implement improvements.
See www.srfsteleinfra.in for the most current information. Revised: 19 Jan 2023

