


SRFS TELEINFRA

800-2700MHz 3 dBi Magnetic Mount Antenna with SMA RG 174 Cable

Get connected with us:



Electrical Specifications	
Frequency Range	800-2700 MHz
Gain	3 dBi
VSWR	< 1.5
Return Loss	-15dB
Impedance	50Ω
Polarization	Vertical
Radiation Direction	Omni Directional
Impedance	50 Ohm
Lightning Protection	Direct Ground
Maximum Input Power	100 W
HPBW	H:360°; V: 30°/40°
Mechanical Specifications	
Cable	RG174 3 Mtr or Customized
Connector	SMA (M) or Customized
Antenna Mount	Magnetic Base
Antenna Length	200mm
Magnetic Base Dia	30mm
Operating Temperature	-40°C ~85°C
Humidity	5~95%
Environmental Friendly	ROHS Compliant
IP Rating	IP65



Add: plot no 10 shiv vihar a block Najafgarh Sahibi river road Vikasnagar Uttam nagar new delhi-110059

+91 84354 74330 info@srfsteleinfra.in, aayush@srfsteleinfra.in

www.srfsteleinfra.in, www.srfsteleinfra.com

SRFS Teleinfra | All specifications are subject to change.
SRFS reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.
It may be necessary to make modifications to the part and/or the documentation of the part to implement improvements.
See www.srfsteleinfra.in for the most current information. Revised: 19 Jan 2023

