

# SRFS TELEINFRA

## GSM Sticker Antenna with SMA Male Straight Connector

Get connected with us:



Electrical Specifications	
Frequency Range	698-960/1710-2700 MHz
Gain	3 dBi
VSWR	<=2.0
Return Loss	-15dB
Impedance	50Ω
Polarization	Vertical
Radiation Direction	Omni Directional
Impedance	50 Ohm
Lightning Protection	Direct Ground
Maximum Input Power	50 W
Antenna Radome Material	ABS
Mechanical Specifications	
Cable	RG174 3 Mtr
Connector	SMA (M)
Antenna Mount	Sticker
Antenna Dimension	22 X 115 mm
Weight	45 gm
Operating Temperature	-40°C ~85°C
Humidity	5~95%
Environmental Friendly	ROHS Compliant
IP Rating	IP65

Add: plot no 10 shiv vihar a block Najafgarh Sahibi river road Vikasnagar Uttam nagar new delhi-110059

+91 84354 74330 info@srfsteleinfra.in, aayush@srfsteleinfra.in

www.srfsteleinfra.in, www.srfsteleinfra.com

SRFS Teleinfra | All specifications are subject to change.  
SRFS reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.  
It may be necessary to make modifications to the part and/or the documentation of the part to implement improvements.  
See www.srfsteleinfra.in for the most current information. Revised: 19 Jan 2023

