

SRFS TELEINFRA

Get connected with us:



RG 316 CABLE DS (DOUBLE SHIELDED)



CONSTRUCTION		
Item	Material	Diameter (mm)
Inner Conductor	Silver plated copper covered steel	0.51
Dielectric	PTFE	1.52
First Shield	Silver plated Copper Braid	
Second Shield	Silver plated Copper Braid	2.39
Jacket	FEP, Tan	2.9 mm
ELECTRICAL SPECIFICATION		
Cutoff Frequency	3Ghz	
Impedance (Ω)	50 \pm 2	
Capacitance (pF/m)	29.4pF/ft (96.46pF/m)	
Shielding Effectiveness	90dB	
Inner Conductor	4.28ohms/1000ft(14.1ohms/km)	
Outer Conductor	3.89ohms/1000ft(12.8ohms/km)	
Voltage withstand (Vrms)	1200VoltsDC	
Bend Radius	0.59 (14.99mm)	
Velocity of Propagation	70%	
Operating Temperature Range	-55 to 200 °C	
ATTENUATION AT 20°C (dB/100m)		
Frequency (MHz)	Maximum (dB / 100 ft)	
10	2.5	
30	4.3	
50	5.6	
100	8	
400	16	
1000	26	
1500	32	
2000	38	
2500	42	

Add: plot no 10 shiv vihar a block Najafgarh Sahibi river road Vikas Nagar Uttam nagar new delhi-110059

+91 7838349349, +91 8076749052 info@srfsteleinfra.in, sales@srfsteleinfra.in, srfsteleinfra@gmail.com

www.srfsteleinfra.in, www.srfsteleinfra.com

SRFS Teleinfra | All specifications are subject to change.
SRFS reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.
It may be necessary to make modifications to the part and/or the documentation of the part to implement improvements.
See www.srfsteleinfra.in for the most current information. Revised: 19 Jan 2023

