

SRFS TELEINFRA

RG 58 White Cable

Get connected with us:



CONSTRUCTION		
Item	Material	Diameter (mm)
Conductor	Tinned Copper	0.9
Insulation	Solid PE	2.95
Braiding Layer	Tinned Copper	94%
Jacket	LSZH	4.95
ELECTRICAL SPECIFICATION		
Operating Temperature Range		-30°C to +80°C
Impedance (Ω)		50 \pm 3
Rated Voltage(V)		1,900V rms
Capacitance (pF/m)		100 \pm 5
Velocity Ratio (%)		66
Max. Conductor DC Resistance at 20°C (Ω /km)		39.2
Min. Insulation DC Resistance at 20°C ($M\Omega \times km$)		>500
Operating Temperature Range		-30°C to +80°C
ATTENUATION AT 20°C (dB/100m)		
Frequency (MHz)		
100MHz		21
200 MHz		31
1,000MHz		76

Add: plot no 10 shiv vihar a block Najafgarh Sahibi river road Vikasnagar Uttam nagar new delhi-110059

+91 84354 74330 info@srfsteleinfra.in, aayush@srfsteleinfra.in, srfsteleinfra@gmail.com

www.srfsteleinfra.in, www.srfsteleinfra.com

SRFS Teleinfra | All specifications are subject to change.
SRFS reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.
It may be necessary to make modifications to the part and/or the documentation of the part to implement improvements.
See www.srfsteleinfra.in for the most current information. Revised: 19 Jan 2023

