

SRFS TELEINFRA

Get connected with us:



698-2700MHz 12 dBi Patch Panel Antenna with SMA (M)

RP Outdoor



Technical Specifications		
Frequency Range	698-960 MHz	1710-2700 MHz
Gain	9 dBi	12 dBi
VSWR	≤ 2.0	$< =1.7$
PIM, 3rd Order, 2x20W	≤ -130 dBc	
Polarization	Vertical	
Front to Back Ratio	≥ 13 dB	
Horizontal Beam width	65°	
Vertical Beam width	55°	
Impedance	50 Ohm	
Lightning Protection	DC Ground	
Max.Power	100 W	
Mechanical Specifications		
Cable	RG58 5 Mtr or Customized	
Connector	SMA (M) RP or Customized	
Antenna Dimension(mm)	168x158x50 mm	
Weight	1.1kg	
Reflector Material	Aluminum/PCB	
Radom Material	ABS /PP	
Rated Wind Velocity	210 km/h	
Relative Humidity	5~95%	
Operating Temperature	-40°C to +65 °C	

Add: plot no 10 shiv Vihar a block Najafgarh Sahibi river road Vikas Nagar Uttam Nagar new delhi-110059

+91 84354 74330 info@srfsteleinfra.in, aayush@srfsteleinfra.in

www.srfsteleinfra.in, www.srfsteleinfra.com

SRFS Teleinfra | All specifications are subject to change.
SRFS reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.
It may be necessary to make modifications to the part and/or the documentation of the part to implement improvements.
See www.srfsteleinfra.in for the most current information. Revised: 19 Jan 2023

