

SRFS TELEINFRA


Get connected with us:




2.5-3.5 dBi Omni Ceiling Antenna 698-960/1710-2700MHz



ELECTRICAL SPECIFICATIONS		
Frequency Range	698-960 MHz	1710-2700 MHz
Gain (Avg)	2.5 dBi	3.5 dBi
VSWR (max)	≤1.8	≤1.5
Polarization	Vertical	
Horizontal Beamwidth	360°	
Vertical Beamwidth	90°/55°	
Input Impedance	50Ω	
Lightning Protection	DC Ground	
Maxpower	50 W	
MECHANICAL SPECIFICATIONS		
Connector	N-Female	
Dimensions	Ø186×86 mm	
Packing Size	170×180×180 mm	
Weight	0.25 kg	
Reflector Material	Aluminum	
Radome Material	ABS	
Operating Temperature	-40°C to +65 °C	



H-Plane



V-Plane

Add: plot no 10 shiv Vihar a block Najafgarh Sahibi river road Vikas Nagar Uttam Nagar new delhi-110059

+91 84354 74330 info@srfsteleinfra.in, aayush@srfsteleinfra.in

www.srfsteleinfra.in, www.srfsteleinfra.com

SRFS Teleinfra | All specifications are subject to change.
SRFS reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.
It may be necessary to make modifications to the part and/or the documentation of the part to implement improvements.
See www.srfsteleinfra.in for the most current information. Revised: 19 Jan 2023

