

SRFS TELEINFRA


Get connected with us:




3dBm MIMO Omni Ceiling Antenna 698-960_1710-2700MHz



ELECTRICAL SPECIFICATIONS					
Frequency Range	698-800MHz	800-960MHz	1710-2700MHz	1710-1880MHz	1880-2700MHz
Gain (Avg)	≥1.5 dBi		≥3.5 dBi	≥4 dBi	
VSWR (max)	≤1.8	≤1.5	≤1.5	≤1.8	≤1.5
Polarization	Horizontal			Vertical	
Isolation	≥26dB				
Horizontal Beamwidth	H: 360°/E: 85°/55°				
Vertical Beamwidth	H: 360°/E: 55°/45°				
Input Impedance	50Ω				
Lightning Protection	DC Ground				
Maxpower	50 W				
MECHANICAL SPECIFICATIONS					
Connector	2×N-female				
Dimensions	Ø182×123 mm				
Packing Size	170×180×180 mm				
Weight	0.37 kg				
Reflector Material	Brass				
Radome Material	ABS				
Operating Temperature	-40°C to +65 °C				



H-Plane



V-Plane

Add: plot no 10 shiv Vihar a block Najafgarh Sahibi river road Vikas Nagar Uttam Nagar new delhi-110059

+91 84354 74330 info@srfsteleinfra.in, aayush@srfsteleinfra.in

www.srfsteleinfra.in, www.srfsteleinfra.com

SRFS Teleinfra | All specifications are subject to change.
SRFS reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.
It may be necessary to make modifications to the part and/or the documentation of the part to implement improvements.
See www.srfsteleinfra.in for the most current information. Revised: 19 Jan 2023

