

SRFS TELEINFRA


Get connected with us:




4dBi Omnidirectional Antenna 698-960/1710-2700MHz



ELECTRICAL SPECIFICATIONS		
Frequency Range	698-960 MHz	1710-2700 MHz
Gain (Avg)	4 dBi	4 dBi
VSWR (max)	≤2.0	≤1.8
Polarization	Vertical	
Horizontal Beamwidth	360°	
Vertical Beamwidth	60°	
Input Impedance	50Ω	
Lightning Protection	DC Ground	
Maxpower	100 W	
MECHANICAL SPECIFICATIONS		
Connector	N-Female	
Dimensions	Ø63×250 mm	
Packing Size	350×90×90 mm	
Weight	1.0 kg	
Reflector Material	Copper	
Radome Material	UV-PVC	
Operating Temperature	-40°C to +65 °C	
Rated Wind Velocity	210 km/h	
Mounting Pole	Ø38-Ø52 mm	



H-Plane



V-Plane

Add: plot no 10 shiv Vihar a block Najafgarh Sahibi river road Vikas Nagar Uttam Nagar new delhi-110059

+91 84354 74330 info@srfsteleinfra.in, aayush@srfsteleinfra.in

www.srfsteleinfra.in, www.srfsteleinfra.com

SRFS Teleinfra | All specifications are subject to change.
SRFS reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.
It may be necessary to make modifications to the part and/or the documentation of the part to implement improvements.
See www.srfsteleinfra.in for the most current information. Revised: 19 Jan 2023

