


SRFS TELEINFRA

698-2700MHz Low PIM MIMO Indoor Dome Antenna


Get connected with us:



Electrical Specifications					
Port	Port1			Port2	
Center Frequency, MHz	698-800	800-960	1710-2700	1710-1880	1880-2700
Gain dBi	≥1.5	≥3.5		≥4	
VSWR	≤1.8	≤1.5	≤1.5	≤1.8	≤1.5
Polarization	Vertical			Horizontal	
Isolation	≥26 dB				
PIM, 3rd Order, 2x20W	≤-150 dBc				
Horizontal Beamwidth	360°				
Vertical Beamwidth	55°	45°		45°	
Maximum Input Power	50W				
Input Impedance	50 Ω				
Lightning Protection	DC Ground				
Mechanical Specifications					
Connector	2xN-Female				
Dimensions	Ø182x123 mm				
Packing Size	170x180x180 mm				
Weight	0.37 kg				
Reflector Material	Aluminum and PCB				
Radom Material	ABS (UV Stabilized)				
Operating Temperature (°C)	-40°C to +55 °C				



H-Plane



V-Plane

Add: plot no 10 shiv vihar a block Najafgarh Sahibi river road Vikasnagar Uttam nagar new delhi-110059

+91-9027232570, +91-8800726650, +91 8076749052 info@srfsteleinfra.in, info@srfsteleinfra.com, srfsteleinfra@gmail.com

www.srfsteleinfra.in, www.srfsteleinfra.com

SRFS Teleinfra | All specifications are subject to change.
SRFS reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.
It may be necessary to make modifications to the part and/or the documentation of the part to implement improvements.
See www.srfsteleinfra.in for the most current information. Revised: 19 Jan 2023

