

SRFS TELEINFRA


Get connected with us:




698-2700MHz Low PIM MIMO Panel Antenna



Electrical Specifications			
Frequency Range, MHz	698-960	1710-2700	1710-2700
Gain, dBi	6	8	8
VSWR	≤2.0	≤1.5	≤1.5
Polarization	Vertical		
PIM, 3rd Order, 2x20W	≤-150 dBc		
Front to Back Ratio	≥10 dB	≥20 dB	≥20 dB
Horizontal Beamwidth	90°	65°	65°
Vertical Beamwidth	68°	60°	60°
Maximum Input Power	50W		
Input Impedance	50 Ω		
Lightning Protection	DC Ground		
Mechanical Specifications			
Connector	2xN-Female		
Dimensions	260x170x60 mm		
Packing Size	350x260x80 mm		
Weight	0.75 kg		
Reflector Material	Aluminum and PCB		
Radome Material	ABS (UV Stabilized)		
Rated Wind Velocity	210 km/h		
Environmental Friendly	ROHS Compliant		
Operating Temperature (°C)	40°C to +65 °C		
Mounting Pole	Ø38-Ø52 mm		



H-Plane



V-Plane

Add: plot no 10 shiv vihar a block Najafgarh Sahibi river road Vikasnagar Uttam nagar new delhi-110059

+91-9027232570, +91-8800726650, +91 8076749052 info@srfsteleinfra.in, info@srfsteleinfra.com, srfsteleinfra@gmail.com

www.srfsteleinfra.in, www.srfsteleinfra.com

SRFS Teleinfra | All specifications are subject to change.
SRFS reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.
It may be necessary to make modifications to the part and/or the documentation of the part to implement improvements.
See www.srfsteleinfra.in for the most current information. Revised: 19 Jan 2023

