

SRFS TELEINFRA


Get connected with us:




698-4000MHz 3dBi Omni Ceiling Antenna



Electrical Specifications				
Center Frequency, MHz	698-806	806-960	1690-2700	3300-4000
Gain dBi	1.5	2.0	3.0	4.0
VSWR	≤1.8	≤1.5	≤1.5	≤1.5
Polarization	Vertical			
PIM, 3rd Order, 2x20W	≤-150 dBc			
Horizontal Beamwidth	360°			
Vertical Beamwidth	95°	80°	38°	32°
Maximum Input Power	50W			
Input Impedance	50 Ω			
Lightning Protection	DC Ground			
Mechanical Specifications				
Connector	N-Female			
Dimensions	Ø200×120 mm			
Weight	0.4 kg			
Radome Material	ABS (UV Stabilized)			
Operating Temperature (°C)	-40°C to +65 °C			



H-Plane



V-Plane

Add: plot no 10 shiv vihar a block Najafgarh Sahibi river road Vikasnagar Uttam nagar new delhi-110059

+91 84354 74330 info@srfsteleinfra.in, aayush@srfsteleinfra.in

www.srfsteleinfra.in, www.srfsteleinfra.com

SRFS Teleinfra | All specifications are subject to change.
SRFS reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.
It may be necessary to make modifications to the part and/or the documentation of the part to implement improvements.
See www.srfsteleinfra.in for the most current information. Revised: 19 Jan 2023

