


SRFS TELEINFRA

698-4000MHz Low PIM Slim Omni Antenna


Get connected with us:



Electrical Specifications					
Center Frequency, MHz	698-960	1690-2170	2300-2500	2500-2700	3300-4000
Gain dBi	3.0	4.0	4.0	5.0	3.0
VSWR	≤1.8	≤1.8	≤1.8	≤1.8	≤2.0
Polarization	Horizontal				
PIM, 3rd Order, 2x20W	≤-150 dBc				
Horizontal Beamwidth	360°				
Vertical Beamwidth	120°	85°	76°	70°	62°
Maximum Input Power	50W				
Input Impedance	50 Ω				
Lightning Protection	DC Ground				
Mechanical Specifications					
Connector	N-Female				
Dimensions	Ø190x7.3 mm				
Weight	0.25 kg				
Reflector Material	PCB				
Color	White				
Radome Material	ABS (UV Stabilized)				
Operating Temperature (°C)	-40°C to +65 °C				



H-Plane



V-Plane

Add: plot no 10 shiv vihar a block Najafgarh Sahibi river road Vikasnagar Uttam nagar new delhi-110059

+91 84354 74330 info@srfsteleinfra.in, aayush@srfsteleinfra.in

www.srfsteleinfra.in, www.srfsteleinfra.com

SRFS Teleinfra | All specifications are subject to change.
SRFS reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.
It may be necessary to make modifications to the part and/or the documentation of the part to implement improvements.
See www.srfsteleinfra.in for the most current information. Revised: 19 Jan 2023

