

SRFS TELEINFRA


Get connected with us:




698-960/1710-2700MHz 4dBi Omni directional Antenna



ELECTRICAL SPECIFICATIONS		
Frequency Range	698-960 MHz	1710-2700 MHz
Gain (Avg)	4 dBi	4 dBi
VSWR (max)	≤1.7	≤1.6
Polarization	Vertical	
Horizontal Beamwidth	360°	
Vertical Beamwidth	60°	
Input Impedance	50Ω	
Lightning Protection	DC Ground	
Maxpower	100 W	
MECHANICAL SPECIFICATIONS		
Connector	N-Female	
Dimensions	190×66×66 mm	
Packing Size	280×90×90 mm	
Weight	0.35 kg	
Reflector Material	Copper	
Radome Material	UV-PVC	
Operating Temperature	-40°C to +65 °C	
Rated Wind Velocity	210 km/h	
Mounting Pole	Ø38-Ø52 mm	



H-Plane



V-Plane

Add: plot no 10 shiv Vihar a block Najafgarh Sahibi river road Vikas Nagar Uttam Nagar new delhi-110059

+91 84354 74330 info@srfsteleinfra.in, aayush@srfsteleinfra.in

www.srfsteleinfra.in, www.srfsteleinfra.com

