

# SRFS TELEINFRA


Get connected with us:




698-960/1710-2700MHz MIMO Ceiling Antenna



ELECTRICAL SPECIFICATIONS						
Port	Port1			Port2		
Frequency Range	698-960MHz	1710-2170MHz	2400-2700MHz	698-960MHz	1710-2170MHz	2400-2700MHz
Gain (Avg)	3.0 dBi	4.5 dBi		3.0 dBi	4.5 dBi	
VSWR (max)	≤2.0	≤1.7		≤2.0	≤1.7	
Polarization	Vertical			Vertical		
Isolation	>20 dB	>25 dB		>20 dB	>25 dB	
Horizontal Beamwidth	115°					
Vertical Beamwidth	110°					
Input Impedance	50Ω					
Lightning Protection	DC Ground					
Maxpower	50 W					
MECHANICAL SPECIFICATIONS						
Connector	2×N-female					
Dimensions	38×210 mm					
Shipping Dimensions	155×120×225 mm					
Weight	0.45 kg					
Reflector Material	Brass and PCB					
Radome Material	ABS					
Operating Temperature	-40°C to +65 °C					
Mounting	Ceiling Mount					



H-Plane



V-Plane

Add: plot no 10 shiv Vihar a block Najafgarh Sahibi river road Vikas Nagar Uttam Nagar new delhi-110059

+91 84354 74330 info@srfsteleinfra.in, aayush@srfsteleinfra.in

www.srfsteleinfra.in, www.srfsteleinfra.com

SRFS Teleinfra | All specifications are subject to change.  
SRFS reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.  
It may be necessary to make modifications to the part and/or the documentation of the part to implement improvements.  
See www.srfsteleinfra.in for the most current information. Revised: 19 Jan 2023

