

SRFS TELEINFRA

RG 141/RG 402 Coaxial Cable

Get connected with us:



Electrical & Mechanical Specifications		
Frequency Range	33 GHz	
Capacitance	92 pF/m	
Velocity of Propagation	71 %	
Signal Delay	4.7 ns/m	
Insulation Resistance	> 1× 108 MΩm	
Min Screening Effectiveness	> 100 dB (up to 18 GHz)	
Max. Operating Temperature	1.9 KVrms (at sea Level)	
Test Voltage	5 KVrms (50Hz /1 min)	
Impedance	50 Ω + 2	
Temperature Range	-65°C to 165°C	
Material & Finish		Diameter
Centre Conductor	Copper, Silver Plated Wire	0.95mm
Dielectric	PTFE	2.95mm
Outer Conductor	Copper, Tin Plated	3.58mm

INNOVATIONS IN TELECOM WORLD

Add: plot no 10 shiv vihar a block Najafgarh Sahibi river road Vikasnagar Uttam nagar new delhi-110059

+91 84354 74330 info@srfsteinfra.in, aayush@srfsteinfra.in, srfsteinfra@gmail.com

www.srfsteinfra.in, www.srfsteinfra.com

SRFS Teleinfra | All specifications are subject to change.
SRFS reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.
It may be necessary to make modifications to the part and/or the documentation of the part to implement improvements.
See www.srfsteinfra.in for the most current information. Revised: 19 Jan 2023

