

# SRFS TELEINFRA

## DIN Female To N-Male ADAPTOR

Get connected with us:



ELECTRICAL & MECHANICAL SPECIFICATIONS		
Characteristic Impedance	50 ohm	
Frequency Range	DC-6 GHz	
VSWR	$\leq 1.10$ @DC-3 GHz	
Insertion Loss	$\leq 0.10$ dB	
Durability	Mating Cycles $\geq 500$	
MATERIAL & PLATING		
	Material	Plating
Body	Brass	Ni
Insulator	PTFE(Teflon)	-
Center Conductor	Phosphor	Au
ENVIRONMENTAL SPECIFICATION		
Operating Temperature Range	$-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$	
ROHS	Compliant	
Waterproof Rate	IP67	

Add: plot no 10 shiv Vihar a block Najafgarh Sahiba river road Vikas Nagar Uttam nagar new delhi-110059

+91-8435474330, +91-8800726650, +91 8076749052 [info@srfsteleinfra.in](mailto:info@srfsteleinfra.in), [aayush@srfsteleinfra.in](mailto:aayush@srfsteleinfra.in), [srfsteleinfra@gmail.com](mailto:srfsteleinfra@gmail.com)

[www.srfsteleinfra.in](http://www.srfsteleinfra.in), [www.srfsteleinfra.com](http://www.srfsteleinfra.com)

