

SRFS TELEINFRA

GPS/GSM COMBO ANTENNA

Get connected with us:



Electrical Specifications	
Frequency Range	1575.42/824-2170 MHz
Gain	28 dBi
VSWR	< =2
Return Loss	-15dB
Impedance	50 Ohm
Lightning Protection	DC Ground
Maximum Input Power	100 W
Polarization	R.H.C.P
Mechanical & Environmental Specifications	
Antenna Dimension	80*14
Connector	2*SMA (M) or Customized
Cable	RG174 3 Mtr or Customized
Weight	150gm
Mounting	Adhesive mount, Antenna facing toward mounting tape
Housing Material	ABS
Humidity	5~95%
Environmental Friendly	ROHS Compliant
Operating Temperature (°C)	-40°C ~85°C
IP Rating	IP65

Add: plot no 10 shiv vihar a block Najafgarh Sahibi river road Vikasnagar Uttam nagar new delhi-110059

+91 7838349349, +91 8076749052 info@srfsteleinfra.in, srfsteleinfra@gmail.com

www.srfsteleinfra.in, www.srfsteleinfra.com

SRFS Teleinfra | All specifications are subject to change.
SRFS reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.
It may be necessary to make modifications to the part and/or the documentation of the part to implement improvements.
See www.srfsteleinfra.in for the most current information. Revised: 19 Jan 2023

