

SRFS TELEINFRA

N Male R/A 1/2" Super Flex Connector

Get connected with us:



| Electrical & Mechanical Specifications | | |
|--|--|---------|
| Frequency Range | DC 7.5 GHz | |
| Characteristic Impedance | 50 Ω | |
| VSWR | ≤ 1.10 @DC-3GHz | |
| Dielectric Withstanding Voltage | 2500Vrms, 50 Hz at sea level | |
| Test Voltage DC | 2000 V | |
| Dielectric Resistance | $\geq 5000M\Omega$ | |
| Contact Resistance | Center Contact ≤ 1 m Ω Outer Contact ≤ 0.25 m Ω | |
| Average Power | 0.6 KW @ 900 MHz | |
| Peak Power | 10.00 KW | |
| Durability | Mating cycles ≥ 500 | |
| Material & Plating | | |
| | Material | Plating |
| Body | Brass | Ni |
| Insulator | PTFE | - |
| Contact | Brass | Au |
| Ferrule | Brass | Ni |
| Environmental | | |
| Temperature Range | -40°C~+85°C | |
| RoHS | Compliant Yes | |

Add: plot no 10 shiv Vihar a block Najafgarh Sahiba river road Vikas Nagar Uttam nagar new delhi-110059

+91-8435474330, +91-8800726650, +91 8076749052 info@srfsteleinfra.in, aayush@srfsteleinfra.in, srfsteleinfra@gmail.com

www.srfsteleinfra.in, www.srfsteleinfra.com

